

# DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
 Date of first issue: 01/13/2015

## SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Product code : 000000000001595709

### Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road  
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

### Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

## SECTION 2. HAZARDS IDENTIFICATION

### GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

### GHS label elements

Not a hazardous substance or mixture.

Precautionary Statements : **Prevention:**  
P271 Use only outdoors or in a well-ventilated area.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone elastomer

### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Calcium carbonate treated with stearic acid	Not Assigned	>= 51 - <= 52
Amorphous fumed silica	112945-52-5	>= 3 - <= 4
Carbon black	1333-86-4	>= 0.46 - <= 0.94
Quartz	14808-60-7	>= 0.2 - <= 0.21
Methanol	67-56-1	>= 0.18 - <= 0.19

# DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
 Date of first issue: 01/13/2015

## SECTION 4. FIRST AID MEASURES

- |   |   |   |
|---|---|---|
| General advice  | : | In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.  |
| If inhaled  | : | If inhaled, remove to fresh air.<br>Get medical attention.  |
| In case of skin contact                                     | : | In case of contact, immediately flush skin with soap and plenty of water.<br>Remove contaminated clothing and shoes.<br>Get medical attention.<br>Wash clothing before reuse.<br>Thoroughly clean shoes before reuse. |
| In case of eye contact                                      | : | Flush eyes with water as a precaution.<br>Get medical attention if irritation develops and persists.  |
| If swallowed  | : | If swallowed, DO NOT induce vomiting.<br>Get medical attention.<br>Rinse mouth thoroughly with water.   |
| Most important symptoms and effects, both acute and delayed | : | None known.   |
| Protection of first-aiders                                  | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.   |
| Notes to physician  | : | Treat symptomatically and supportively.   |

## SECTION 5. FIRE-FIGHTING MEASURES

- |                                       |   |  |
|---------------------------------------|---|--|
| Suitable extinguishing media          | : | Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical                 |
| Unsuitable extinguishing media        | : | None known.  |
| Specific hazards during fire fighting | : | Vapors may form explosive mixtures with air.<br>Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products         | : | Carbon oxides<br>Metal oxides<br>Formaldehyde<br>Silicon oxides  |
| Specific extinguishing meth-          | : | Use extinguishing measures that are appropriate to local cir-  |

## DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 03/09/2017
5.0	09/14/2017	1099131-00010	Date of first issue: 01/13/2015

ods cumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.

## DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version  
5.0Revision Date:  
09/14/2017SDS Number:  
1099131-00010Date of last issue: 03/09/2017  
Date of first issue: 01/13/2015

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate treated with stearic acid	Not Assigned	TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Amorphous fumed silica	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	3 mg/m <sup>3</sup>	ACGIH
Quartz	14808-60-7	TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m <sup>3</sup>	NIOSH REL
		ST	250 ppm 325 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1

## DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
 Date of first issue: 01/13/2015

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Calcium carbonate treated with stearic acid

Amorphous fumed silica

Carbon black

Quartz

**Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Material : Chemical-resistant gloves

Remarks : For prolonged or repeated contact use protective gloves. Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
 Skin contact must be avoided by using impervious protective

# DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 03/09/2017
5.0	09/14/2017	1099131-00010	Date of first issue: 01/13/2015

---

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	black
Odor	:	slight
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	91 °C Method: Seta closed cup
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Self-ignition	:	The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	No data available
Relative density	:	1.52
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-	:	No data available

**DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK**

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
Date of first issue: 01/13/2015

---

octanol/water

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

|| Particle size : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Vapors may form explosive mixture with air.  
Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Methyl alcohol is formed upon contact with water or humid air.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

**Hazardous decomposition products**

Thermal decomposition : Benzene  
Formaldehyde

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact

Ingestion

Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

---

DOW CORNING(R) 795 SILICONE BUILDING  
SEALANT, BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 03/09/2017
5.0	09/14/2017	1099131-00010	Date of first issue: 01/13/2015

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Ingredients:****Amorphous fumed silica:**

Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Information taken from reference works and the literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials  
Information taken from reference works and the literature.

**Carbon black:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.0046 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

**Quartz:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**Methanol:**

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg  
Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment  
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate (Humans): 300 mg/kg  
Method: Expert judgment

**DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK**

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
Date of first issue: 01/13/2015

---

**Skin corrosion/irritation**

Not classified based on available information.

**Ingredients:**

**Amorphous fumed silica:**

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials  
Information taken from reference works and the literature.

**Carbon black:**

Species: Rabbit  
Result: No skin irritation

**Methanol:**

Species: Rabbit  
Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Ingredients:**

**Amorphous fumed silica:**

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials  
Information taken from reference works and the literature.

**Carbon black:**

Species: Rabbit  
Result: No eye irritation

**Methanol:**

Species: Rabbit  
Result: No eye irritation

**Respiratory or skin sensitization**

**Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:**

**Carbon black:**

Test Type: Buehler Test  
Routes of exposure: Skin contact

DOW CORNING(R) 795 SILICONE BUILDING  
SEALANT, BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 03/09/2017
5.0	09/14/2017	1099131-00010	Date of first issue: 01/13/2015

Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative

**Methanol:**

Test Type: Maximization Test  
Routes of exposure: Skin contact  
Species: Guinea pig  
Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:****Carbon black:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Methanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Ingredients:****Quartz:**

Species: Humans  
Application Route: inhalation (dust/mist/fume)  
Result: positive  
Remarks: IARC: (International Agency for Research on Cancer)  
These substance(s) are inextricably bound in the product and therefore do not contribute to a  
dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**Methanol:**

Species: Mouse

DOW CORNING(R) 795 SILICONE BUILDING  
SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
Date of first issue: 01/13/2015

Application Route: inhalation (vapor)  
Exposure time: 18 Months  
Result: negative

**IARC**

Group 1: Carcinogenic to humans

Quartz      14808-60-7

Group 2B: Possibly carcinogenic to humans

Carbon black      1333-86-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

Known to be human carcinogen

Quartz      14808-60-7

**Reproductive toxicity**

Not classified based on available information.

**Ingredients:****Methanol:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Mouse  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: Ingestion  
Result: positive  
Remarks: The effects were seen only at maternally toxic doses.

**STOT-single exposure**

Not classified based on available information.

**Ingredients:****Methanol:**

Target Organs: Eyes, Central nervous system  
Assessment: Causes damage to organs.

**STOT-repeated exposure**

Not classified based on available information.

**Ingredients:****Carbon black:**

Routes of exposure: inhalation (dust/mist/fume)

DOW CORNING(R) 795 SILICONE BUILDING  
SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
Date of first issue: 01/13/2015

---

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**Quartz:**

Routes of exposure: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**Repeated dose toxicity****Ingredients:****Carbon black:**

Species: Rat

NOAEL: 1 mg/m<sup>3</sup>

LOAEL: 7 mg/m<sup>3</sup>

Application Route: Inhalation

Test atmosphere: dust/mist

Exposure time: 90 Days

Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Quartz:**

Species: Humans

LOAEL: 0.053 mg/m<sup>3</sup>

Application Route: Inhalation

Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Methanol:**

Species: Rat

NOAEL: 1.06 mg/l

Application Route: inhalation (vapor)

Exposure time: 90 Days

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Carbon black:**

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

DOW CORNING(R) 795 SILICONE BUILDING  
SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
Date of first issue: 01/13/2015

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 5,600 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

**Quartz:****Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Methanol:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l  
Exposure time: 200 h

Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 3 h

**Persistence and degradability****Ingredients:****Methanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 95 %  
Exposure time: 20 d

**Bioaccumulative potential****Ingredients:****Methanol:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): < 10

Partition coefficient: n- : log Pow: -0.77

DOW CORNING(R) 795 SILICONE BUILDING  
SEALANT, BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 03/09/2017
5.0	09/14/2017	1099131-00010	Date of first issue: 01/13/2015

|| octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	5000	*
Toluene	108-88-3	1000	*
Ethylenediamine	107-15-3	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

## DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
 Date of first issue: 01/13/2015

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylenediamine	107-15-3	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**US State Regulations****Pennsylvania Right To Know**

Calcium carbonate treated with stearic acid	Not Assigned
Dimethyl siloxane, hydroxy-terminated	70131-67-8
Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9
Amorphous fumed silica	112945-52-5
Methanol	67-56-1
Toluene	108-88-3

**California Prop. 65**

WARNING: This product can expose you to chemicals including Methanol, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Permissible Exposure Limits for Chemical Contaminants**

Calcium carbonate treated with stearic acid	Not Assigned
Amorphous fumed silica	112945-52-5

**California Regulated Carcinogens**

Quartz	14808-60-7
--------	------------

**The ingredients of this product are reported in the following inventories:**

NZIoC	: All ingredients listed or exempt.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
ENCS/ISHL	: All components are listed on ENCS/ISHL or exempted from inventory listing.
PICCS	: All ingredients listed or exempt.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
REACH	: For purchases from Dow Corning EU legal entities, all

## DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version 5.0      Revision Date: 09/14/2017      SDS Number: 1099131-00010      Date of last issue: 03/09/2017  
 Date of first issue: 01/13/2015

ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.


KECI : All ingredients listed, exempt or notified.

TCSI : All ingredients listed or exempt.

## SECTION 16. OTHER INFORMATION

## Further information

## NFPA:



## HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

**DOW CORNING(R) 795 SILICONE BUILDING  
SEALANT, BLACK**

Version	Revision Date:	SDS Number:	Date of last issue: 03/09/2017
5.0	09/14/2017	1099131-00010	Date of first issue: 01/13/2015

---

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 795 SILICONE BUILDING SEALANT, BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 03/09/2017
5.0	09/14/2017	1099131-00010	Date of first issue: 01/13/2015

---

US / Z8